



SPECIFICATION			UNIT	H09SMH	H12SMH	H18SMH	H24SMH
Capacity	Cooling	Min/Rated/Max	<i>kW</i>	2.55	3.22	4.90	6.00
		Min/Rated/Max	<i>Btu/h</i>	8,701	10,987	16,719	20,473
	Heating	Min/Rated/Max	<i>kW</i>	2.55	3.30	5.20	6.20
		Min/Rated/Max	<i>Btu/h</i>	8,701	11,260	17,743	21,155
Power Input	Cooling	Min/Rated/Max	<i>W</i>	847	1,070	1,628	1,996
	Heating	Min/Rated/Max	<i>W</i>	695	1,000	1,526	1,800
Running Current	Cooling	Min/Rated/Max	<i>A</i>	3.90	5.10	7.50	8.80
	Heating	Min/Rated /Max	<i>A</i>	3.30	4.70	7.20	8.30
EER			<i>W/W</i>	3.01	3.01	3.01	3.01
COP			<i>W/W</i>	3.67	3.30	3.41	3.44
Energy Label Grade		Cooling / Heating	-	B / A++	B / A	B / A+	B / A+
Available Voltage Range			<i>V</i>	-	-	-	-
Power Supply			\emptyset, V, Hz	1, 220 - 240, 50	1, 220 - 240, 50	1, 220 - 240, 50	1, 220 - 240, 50
Indoor	Dimensions	Net	<i>mm</i>	822 × 258 × 203	822 × 258 × 203	890 × 300 × 220	998 × 325 × 227
	Weight	Net	<i>kg</i>	8.0	8.0	10.5	13.0
Outdoor	Dimensions	Net	<i>mm</i>	660 × 482 × 240	715 × 482 × 240	810 × 585 × 280	860 × 650 × 310
	Weight	Net	<i>kg</i>	25.0	26.0	41.0	42.5
Circuit Breaker			<i>A</i>	20	25	40	45
Piping	Size	Liquid	<i>mm</i>	Ø 6.35	Ø 6.35	Ø 6.35	Ø 9.52
		Gas	<i>mm</i>	Ø 9.52	Ø 12.7	Ø 12.7	Ø 15.88
Refrigerant		Type	-	R410A	R410A	R410A	R410A
Compressor		Type	-	Rotary	Rotary	Rotary	Rotary

Note: Specifications, designs, and features are subject to change without prior notice for performance improvement. The values provided above are based on standard testing conditions.